

DECLARATION OF PERFORMANCE

According to Regulation (EU) No 305/2011 of the European Parliament and of the Council on construction products:

DECLARATION OF PERF. NO. 712-1-19.03

PRODUCT: Fabric fire resistant rolling shutter FIBREroll
Product variants "EW30", "EW45", "EW60", "S" and "S200"

PRODUCT IDENTIFICATION: The identification of the product is made using a nameplate, which includes, among other things, the type, product variant, serial number and declared properties

USAGE OF PRODUCT: Vertically sliding rolling door for closing construction openings between adjacent fire compartments

MANUFACTURER: AVAPS s.r.o., U Obalovny 488, 250 67 Klecany, Czech Republic

SYSTEM OF ASSESSMENT: System 1 + System 3

NOTIFIED BODY: Notified body no. 1396 (Fires s.r.o.)

HARMONISED STANDARDS: EN 16034:2014, EN 13241+A2:2016

EN 16034:2014

The notified product verification body FIRES s.r.o. (NO. 1396) has performed the determination of the product type (declaration of performance of the construction product) on base of type (including sampling), calculation for the type, table values product description, initial inspection of the manufacturing company and in-house production control plus continuous monitoring, appraisal and evaluation of the in-house production control and issued the Certificate of constancy of product performance no. 1396-CPR-0154.

EN 13241+A2: 2016

The notified body FIRES s.r.o. (NB. 1396) has performed assessment and verification of constancy of performance and issued the test report Assessment and verification of constancy of performance no. S1396/19/0002/2401/SC.

ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE:

PROPERTY	PERFORMANCE	HARMONIZED STANDARD
Fire resistance	E 30 / EW 30 – type "EW30" E 60 / EW 45 – type "EW45" E 120 / EW 60 – type "EW60", "S", "S200" ¹⁾	EN 16034:2014
Smoke control	S _a – type "S" S _a , S ₂₀₀ – type "S200"	
Ability to release	Released	
Self-closing	C	
Trvanlivost schopnosti uvolnění	Release maintained	
Durability of self-closing (against degradation)	0 ²⁾	
Durability of self-closing (against ageing)	Achieved	
Release of dangerous substances	Product does not release any dangerous substances in excess of the maximum permitted levels	EN 13241+A2:2016
Safe opening	Pass	
Mechanical resistance and stability	Pass	

¹⁾ Fabric fire resist. roll. shutter FIBREroll, type "S" and "S200", with alumin. foil on exposed side has one side classification E 180 / EW 120.

²⁾ Durability of release according to EN 14637 is 10 000 cycles (report FIRES-MP-012-19-AUNE).

Product properties are in line with the properties listed in the table. This declaration of performance is made under the sole responsibility of the manufacturer. Signed by and on behalf of the manufacturer:


AVAPS s.r.o. 16
 U Obalovny 488
 250 67 Klecany
 Tel.: 284 688 545
 IČ: 25650939
 DIČ: CZ 25650939
 Ing. arch. Filip Novotný, CEO

Klecany, 21.10.2019