



CE

Hoefnagels Branddeuren B.V. Zevenheuvelenweg 50 5048 AN Tilburg Netherlands

17

DoP's are available at: www.hoefnagels.com	
HB-DOP-0001	HB-DOP-0002
EN 16034:2014	EN 16034:2014
Firescreen® Temperature T1 EI30	Firescreen® Temperature T2 EI60
Dimensional restrictions:	Dimensional restrictions:
Max. width x height: 5000 x 4000 mm	Max. width x height: 3000 x 2930 mm
Steel zinc-plated/coated material	Steel zinc-plated/coated material
Rigid support structure: possible	Rigid support structure: possible
Fire compartmentation	Fire compartmentation
Resistance to fire:	Resistance to fire:
E: 30	E: 120
EI ₁ : 30	EI ₁ : 30
El ₂ : 30	El ₂ : 60
EW: 30	EW: 120
Smoke control: NPD	Smoke control: NPD
Ability to release: released	Ability to release: released
Self-closing: C	Self-closing: C
Durability of ability to release: NPD	Durability of ability to release: NPD
Durability of self-closing: NPD	Durability of self-closing: NPD

The product is CE marked according to EN 16034 in combination with EN 13241 for the versions mentioned above.

Hoefnagels Branddeuren B.V.
Postbox 5036
5004 EA TILBURG
The Netherlands

+31 134625959 info@hoefnagels.com